LABDEX

Water Jacketed Co2 Incubator LX201WJI

Email: info@labdex.com **website:** www.labdex.com

Description

Water jacketed CO2 Incubator LX201WJI is designed with a microprocessor-based PID controller which provides a precisely controlled, accurate and uniform environment throughout the culturing process. Equipped with fan for forced convection, LED digital display, sterile air filtration devices and UV light system to reduce pollution. It has independent temperature-limiting alarm system for the safe running of experiments.

Specifications

Chamber volume	160 L
Type	Water jacket
Temperature range	RT +3~60°C
Temperature stability	≤±0.2°C
Temperature uniformity	≤±0.3°C
Timing range	1~9999min or without timing
CO2 Range	0~20%
Humidity method	Natural vaporization
Power supply	AC220V, 50HZ
Power rating	900 W
Chamber size (W x D x H)	500 x 500 x 650 mm
Exterior size (W x D x H)	690 x 690 x 1030 mm
Net weight	75 kg
Package size (W x D x H)	700 x 780 x 1180 mm

Gross weight	110 kg

Features

- Build with LED digital display with microprocessor-based PID controller
- It has a forced air convection function
- Having a polished stainless-steel chamber with air duct
- Water and doors are separately controlled by three probes to ensure high accuracy
- UV light system for reducing pollution
- It has safety features like an alarm function for over-heating, lack of water, and unaspirated, and ensuring the safe operation of the instrument
- Provides natural evaporation of humidification to ensure the chamber can maintain good humidity
- The ratio of CO2 gas and air can be arbitrarily selected according to the needs
- Direct reading type flow meter

Applications

- Used in microbiology, life science, pharmacy, food processing, chemical industry, research, education institutes, etc.

Optional Accessories

- Air jacket

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com